

# 12G-SDI Video SFP+ Optical Transmitter, 20km Reach

## FBB-V1231K20CN

**Features**

- SD/HD/3G/6G/12G-SDI SFP Transmitter
- ST 259, ST 292-1,ST 424, ST-2081 and ST-2082 compatible
- Metal enclosure for Lower EMI
- 1310nm DFB laser transmitter
- Supports SDI pathological patterns for SD-SDI, HD-SDI,
- 3G-SDI,6G-SDI and 12G SDI
- ROHS compliant(lead free)
- single 3.3V power supply
- Hot-pluggable SFP footprint
- Operating case temperature range: 0 to +70°C

**Applications**

- Serial Digital Fiber Transmission System for SMPTE ST 259, SMPTE ST 344, SMPTE ST 292-1/2, SMPTE ST 424, SMPTE ST 2081-1 and SMPTE ST 2082-1 Signals
- UHDTV/HDTV/SDTV Service Interfaces

**Description**

FIBERSTAMP's Video transmitter is designed to transmit data rates from 50Mbps to 11.88Gbps, compliant with SMPTE ST 2082-1 (12G UHD-SDI), ST 2081-1 (6G UHD-SDI), ST424 (3G SDI), ST 292-1 (HD-SDI), and ST 259 (SD-SDI). FIBERSTAMP's Video transceiver supports SDI pathological patterns signals.




Figure 1. Module Block Diagram



### Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Supply Voltage	V <sub>cc</sub>	-0.5	4	V
Storage Temperature	T <sub>s</sub>	-40	+85	°C
Operating Humidity	-	5	85	%

### Recommended Operating Conditions

Parameter	Symbol	Min	Typical	Max	Unit
Operating Case Temperature	T <sub>c</sub>	0		+70	°C
Power Supply Voltage	V <sub>cc</sub>	3.13	3.3	3.47	V
Power Supply Current	I <sub>cc</sub>		160		mA
Data Rate			12		Gbps

### Optical and Electrical Characteristics

Parameter	Symbol	Min	Typical	Max	Unit	Notes	
Transmitter							
Center Wavelength	$\lambda_c$	1300	1310	1320	nm		
Spectral Width (-20dB)	$\sigma$			1	nm		
Side Mode Suppression Ratio	SMSR	30			dB		
Average Output Power	P <sub>out</sub>	-3		1	dBm	1	
Extinction Ratio	ER	3.5			dB		
Data Input Swing Differential	V <sub>IN</sub>	400		1000	mV	2	
Input Differential Impedance	Z <sub>IN</sub>	90	100	110	$\Omega$		
Rise/Fall Time (20%~80%)	SD-SDI			1500	ps	3	
	HD-SDI			270			
	3G-SDI			135			
	6G-SDI			80			
	12G-SDI			45			
Output Jitter	Timing Jitter	SD-SDI			0.2	UI	4
		HD-SDI			1		
		3G-SDI			2		
		6G-SDI			4		
		12G-SDI			8		
	Alignment Jitter	SD-SDI			0.2		
		HD-SDI			0.2		
		3G-SDI			0.3		
		6G-SDI			0.3		
		12G-SDI			0.3		



Parameter	Symbol	Min	Typical	Max	Unit	Notes
TX Disable	Disable	2.0		Vcc	V	
	Enable	0		0.8	V	
TX Fault	Fault	2.0		Vcc	V	
	Normal	0		0.8	V	

**Note:**

1. The optical power is launched into SMF.
2. PECL input, internally AC-coupled and terminated.
3. Rise and fall times, 20% to 80%.
4. UI means one period.

**Diagnostics Specification**

Parameter	Range	Unit	Accuracy	Calibration
Tx Disable Negate Time	0 to +70	° C	±3° C	Internal / External
Voltage	3.0 to 3.6	V	±3%	Internal / External
Bias Current	0 to 100	mA	±10%	Internal / External
TX Power	-3to +1	dBm	±3dB	Internal / External

**I2C Bus Interface**

The I2C bus interface uses the 2-wire serial CMOS E2PROM protocol. The serial interface meets the following specifications:

1. Support a maximum clock rate of 280Khz.
2. Input/Output levels comply with LVCMOS/LVTTL or compatible logics.

Low: 0 – 0.8 V

High: 2.0 – 3.3 V

Undefined: 0.8 – 2.0 V

**Pin Description**

Pin	Signal Name	Description	Plug Seq	Notes
1	VEE	Ground	1	
2	VEE	Ground	3	
3	NC	Not Connected	3	
4	VEE	Ground	3	
5	SCL	2-wire Serial Interface Clock	3	Note 2
6	SDA	2-wire Serial Interface Data Line	3	Note 2
7	VEE	Ground	3	
8	NC	Not Connected	3	
9	NC	Not Connected	1	
10	NC	Not Connected	1	
11	VEE	Ground	1	
12	NC	Not Connected	3	
13	NC	Not Connected	3	
14	VEE	Ground	1	



Pin	Signal Name	Description	Plug Seq	Notes
15	VCC	Module 3.3 V Supply	2	
16	VCC	Module 3.3 V Supply	2	
17	VEE	Ground	1	
18	TX+	Transmitter Non-Inverted Data Input	3	Note 3
19	TX-	Transmitter Inverted Data Input	3	Note 3
20	TX_DIS	Transmitter Disable	1	Note 1

**Note:**

Plug Seq.: Pin engagement sequence during hot plugging.

1. TX Disable is an input that is used to shut down the transmitter optical output. It is pulled up within the module with a 4.7k~10kΩ resistor. Its states are:

- Low (0 ~ 0.8V): Transmitter on
- (0.8V~2.0V): Undefined
- High (2.0 ~ 3.46V): Transmitter Disabled
- Open: Transmitter Disabled

2. SCL,SDA: They should be pulled up with a 4.7k~10kΩ resistor on the host board to a voltage between 3.15V and 3.6V.

SCL is the clock line of two wire serial interface for serial ID.

SDA is the data line of two wire serial interface for serial ID.

3. TX-/+: These are the differential transmitter inputs. They are internally AC-coupled, differential lines with 100Ω differential termination inside the module.

**Pin Definition**





Figure 2. Electrical Pin-out Details

**Mechanical Dimensions**



**Figure 3. Mechanical Specifications**

**Regulatory Compliance**

Feature	Standard
Laser Safety	IEC 60825-1:2014 (Third Edition)
Environmental protection	2011/65/EU
CE EMC	EN55032 : 2015 EN55035 : 2017 EN61000-3-2:2014 EN61000-3-3:2013
FCC	FCC Part 15, Subpart B; ANSI C63.4-2014
Product Safety	EN/UL 60950-1, 2nd Edition, 2014-10-14

**⚠ CAUTION:**

Use of controls or adjustment or performance of procedures other than those specified herein may result in hazardous radiation exposure.

**Ordering Information**

Part Number	Product Description
FBB-V1231K20CN	1310nm, 10/20km,SD/HD/3G/6G/12G SDI Single Transmitter, NON-MSA

**Important Notice**

Performance figures,data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by FIBERSTAMP before they become applicable to any particular order or contract. In accordance with the FIBERSTAMP policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of FIBERSTAMP or others. Further details are available from any FIBERSTAMP sales representative.