

Features

- ◆ Compliant OSFP MSA
- ◆ Typical insertion loss less 8dB@26.56GHz with 0.3m length
- ◆ 100ohm differential impedance system
- ◆ 3.3V power supply
- ◆ I2C R/W function
- ◆ Status indicators with LED
- ◆ 3.3V/0.85W fan and heat sink for contact cooling
- ◆ Low EMI radiation and crosstalk
- ◆ RoHS compliant(lead free)

Applications

- ◆ Extend 800G OSFP transceiver/AOC for liquid immersion link environment
- ◆ Protect device OSFP SMT connector
- ◆ provide I2C R/W and some status indicators with LED

Description

FIBERSTAMP can offer rich experience of immersion solution, that includes different form and speed transceivers/AOC/product. FIBERSTAMP 800G OSFP immersion cooling extender (FSOE-PC801-DXX) is an important part of liquid immersion solution, normal OSFP form transceiver/AOC can be used for immersion environment with this product. This product include extender cage, cable, OSFP housing three parts, the cable length can be customized no more than 0.3m for extension, that can avoid the optical lens/engine/interface exposure to the liquid indirectly.

In addition, this product can provide I2C read/write, also can show the status indicators with LED for low speed electrical hardware pins. When insertion and removal frequently, this product can effectively protect the OSFP SMT connector of switch/NIC.

Liquid cooling Advantage




Figure 1. Liquid cooling advantage



As the requirement of data traffic keeping growth and the heat flux emitted by datacenter internal chips increases constantly, traditional air cooling methods are under pressure. Liquid cooling technologies removes the heat more efficiently with dielectric fluids that have high heat capacity to improve the efficiency of energy in datacenter.

FIBERSTAMP solved the lack of optical transceivers which perform reliability in immersion even liquid immersion depth up to 10m, the Liquid cooling optical series transceiver is suitable for liquid cooling server & system, this series product are compatible with fluorinated liquid and mineral oils well.

Immersion cooling extender can also be a important role in liquid immersion solution, existing normal OSFP form transceiver/AOC can be adapted for immersion indirectly.




Figure 2 Immersion cooling extender under liquid

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Storage Temperature	T _s	-20	85	°C
Case Operating Temperature	T _c	0	70	°C
Humidity (non-condensing)	Rh	5	95	%

Recommended Operating Conditions

Parameter	Symbol	Min	Typical	Max	Unit
Supply Voltage	V _{cc}	3.13		3.47	V
Support Power Dissipation	P _m			16	w
Operating Case Temperature	T _c	0		70	°C
Baud Rate per Lane	fd		53.125		GBaud/s

Main Part assembly


- P1:Extender contact
- P2:Extender cable
- P3:Extender housing



Figure 3 OSFP extender main part assembly



Electrical pinout



Mechanical Dimensions




Figure 5. OSFP Mechanical Specifications




Figure 6. OSFP-RHS Mechanical Specifications

Extender housing pin




Figure 7. Extender housing pin



Regulatory Compliance

FIBERSTAMP’s 800G OSFP immersion cooling extender meet the requirements of the following standards:

Feature	Standard
Electrical Safety	EN 62368-1: 2014 IEC 62368-1:2014 UL 62368-1:2014
Environmental protection	Directive 2011/65/EU with amendment(EU)2015/863
CE EMC	EN55032: 2015 EN55035: 2017 EN61000-3-2:2014 EN61000-3-3:2013
FCC	FCC Part 15, Subpart B; ANSI C63.4-2014

Ordering information

Part Number	Length	Description
FSOE-PC801-D03	30cm	800G OSFP extender with high speed cable, with PET jacket , with fan,0.3 meter length as of Figure 5.
FSRE-PC801-D03	30cm	800G OSFP-RHS extender with high speed cable, with PET jacket , with fan, 0.3 meter length as of Figure 5.

- 1.The length (meter) and wire gage of FSOE-PC801-DXX is decimal and can be customizable
- 2.The extender housing also can be customizable as OSFP RHS form.
- 3.Length as “L” of Mechanical Specifications

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by FIBERSTAMP before they become applicable to any particular order or contract. In accordance with the FIBERSTAMP policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of FIBERSTAMP or others. Further details are available from any FIBERSTAMP sales representative.

sales@fiberstamp.com
<http://www.fiberstamp.com>

Revision History

Revision	Date	Description
V0	28-Nov-2025	Advance Release.

